



# 8688 Anti – Silicone Additive

**Description:**

Special additive to be used in car refinishes in the case of silicone contamination.

---

**Suitable Substrates:**

For Genrock 2K Component products

---

**Mixing ratio by volume:**

Add 2% to ready to spray material.

---

**Raw Material:**

Silicone oil solution

---

**Important remarks:**

- For professional use only.
  - Only use 8688 in instances where fish eyes appear due to silicone contamination.
  - Do not exceed the recommended dosage. Adding too much **General** Anti-Silicone can cause problems in the film.
- 

**Cleaning of equipment:** Clean after use with **General** Cleaning thinner.

---



Wear suitable protection

---

**Flash Point:** 23°C (73.4 °F)

---

**Specific Gravity:** 0.896 kg/cm<sup>3</sup>

---

**VOC:** 806 g/Ltr (6.7 lbs/gal)

---

**SDS:** See the safety data sheet

---

The Warnings displayed on the product labels should be followed. The information contained here represents the current state of our knowledge and is intended as a guide to our products and their uses.

**General Paint Co. S.A.L**

P.O. Box: 7623 Beirut – Lebanon – Tel.: 09 925991/2 – Fax: 09 925993 – E-mail: [info@generalpaint.biz](mailto:info@generalpaint.biz)